

FAST INTERCEPTOR CRAFT Â© 1204



GENERAL DESCRIPTION

This outline specification, together with the General Arrangement (drawing nr. 2013.x-0338-010-3), outlines the design of the Fast Interceptor Craft Â© 1204 (FIC Â© 1204).

The FIC Â© 1204 is designed and equipped to perform the following services:

- fast rescue hot zone,
- fast attack craft (gun boat),
- special operations (reconnaissance, etc..),
- transfer of personnel and equipment.

Therefore the vessel has very good capabilities with respect to:

- able to maintain high speeds in adverse weather conditions, up to Sea State 5,
- safety and comfort for passengers and crew,
- good employability.



Dutch Special Marine Group
Steenpad 13
4797 SG Willemstad NB
the Netherlands

T +31 (0)168 47 18 28
E info@dsmg.nl
W www.dsmg.nl

GENERAL TECHNICAL PARTICULARS

Dimensions:

Length overall : 11.40 m
Length between perpendiculars : 9.20 m
Breadth overall : 3.30 m
Breadth, moulded : 2.60 m
Depth at half length, moulded : 0.90 m
Draught aft, approx. : 0.75 m
Air draught, approx. : 3.50 m
Weight (maximum displacement) : 7500 / 9500 kg

Propulsion:

2 / 3 marine diesel engine, total power : 648 bkW @ 3300 rpm
2 / 3 waterjet propulsion unit : Hamiltonjet HJ 292 / (or) Propelled

Performance:

cruise speed ahead : 30 - 40 knots
max. speed ahead : 35 - 55 knots
range (cruise speed) : 200 Nm

Tank capacity:

total storage capacity of fuel oil : 1.10 + m³

